CABINET STANDARD SELECTIONS (Page 1 of 2)

Standard Cabinet Details

Case

Traditional face frame construction using select birch or knotty alder. Face frames are solid 3/4" thick with 1 1/2" stiles and rails. Mortise and tenon joints.

Sides are birch veneered ½" plywood.

For ease of installation, backs are framed with a 3/8" plywood hanging rail.

Base cabinet backs extend to the floor providing optimal structural stability.

Base Cabinets

24" deep to 34 ½" tall base cabinets with raised panels or mission style doors, with concealed hinges (birch or knotty alder per selection).

Upper Cabinets

30" tall 12" deep cabinets with raised panel or mission style doors, with concealed hinges with 3 ½" crown molding (birch or knotty alder per selection).

Pantry Cabinet

24" deep up to 8'-0" high.

Drawers

9/16' thick solid hardwood face, glued and stapled.

Bottoms are 1/4" birch plywood fully captured.

Slides are standard side/undermount.

Doors

Premium full overlay door styles.

Butt doors on all sizes up to 39" wide.

Mortise and Tenon.

Mission is a full overlay birch door with 2 $\frac{1}{4}$ " stiles and rails. The center panel is a $\frac{1}{4}$ " plywood panel.

Standard raised panel full overlay birch door with 2 %" stiles and rails. The reversed raised center panel is solid wood.

Shelves

Standard particle board.

Hinges

6-way adjustable hidden.

CABINET STANDARD SELECTIONS (Page 2 of 2)

